

Regulatory Compliance

This appendix contains information for customers installing systems in the United Kingdom, Europe, and Italy. Refer to the section about your location.

Information for United Kingdom Use Only

Cisco Systems declaration of operating conditions:

The Cisco 2500 Series is designed to meet the requirements of NET1 and NET2.

Warnings

Interconnection directly, or by way of other apparatus, of ports marked:

“Safety Warning — See instructions for use”

with ports marked or not so marked may produce hazardous conditions on the network and that advice should be obtained from a competent engineer before such a connection is made.

The ports marked “Ethernet,” “Token Ring,” “Console,” and “AUX” have a safety warning applied to them as follows:

“These ports do not provide isolation sufficient to satisfy the requirement of BS6301; apparatus connected to these ports should either have been approved to BS6301 or have previously been evaluated against British Telecommunications plc (Post Office) Technical Guides 2 or 26 and given permission to attach; any that other usage will invalidate any approval given to this apparatus.”

This apparatus must be connected to a mains socket outlet with a protective earth contact.

Information for European Community Use Only

Connection of Power Supply. The Gateway Server is intended for use when supplied with power from a supply providing 220-240 VAC, 50/60 Hz up to 5 Amps.

Other usage will invalidate any approval given to this apparatus if as a result it ceases to comply with BS6301: 1989.

The Cisco 2500 Series is brought into service by the supplier.

Information for European Community Use Only

The ports marked “Ethernet,” “Token Ring,” “Console,” and “AUX” are SELV circuits. SELV circuits should only be connected to other SELV circuits.

Information for Use in Italy Only

The following information applies to Cisco 2503 series and 2504 series models used within the country of Italy.

Warnings

AVVERTENZA PER GLI UTENTI DELLA CISCO 2503, 2504 PER CONNESSIONI ISDN ACCESSO BASICO

“Si raccomanda di spegnere il terminale qualora venisse spostato tra due prese dello stesso o di differente bus SO.”

WARNING FOR USERS OF THE CISCO 2503, 2504 FOR BASIC ACCESS ISDN CONNECTIONS

“It is recommended to switch off the terminal equipment when it is moved between two sockets of the same or different bus.”